GE Grid Solutions



FK

Spring Drives for circuit-breakers up to 800 kV and driving energies up to 12 000 J $\,$

GE makes the most of 80 years of experience in design, material selection, development, engineering, manufacturing and servicing of circuit-breaker drives.

Safety First

• Pure-spring design, without pressurized oil

Utmost Experience

- First drives implemented in 1934
- Over 250 000 drives in use

Highest reliability

- Confirmed by IEC / CIGRE
- Field-proven under all operating conditions

Longest Life Duration

- Negligible maintenance costs
- Life-cycle up to 60 years

Outstanding Features

- Energy stability over decades
- Energy independent of temperature, from -50 to +50 °C
- Minimum time scattering

Key Benefits

- Maximum safety
- Field-proven reliability
- First-class availability
- Low total cost of ownership



Applications



550 kV live-tank CB



550 kV dead-tank CB



Generator CB



170 kV live-tank CB



170 kV live-tank CB with single-pole operation



245 kV GIS CB



420 kV GIS single-break CB



145 kV hybrid switchgear



145 kV GIS CB



550 kV GIS CB

CIGRE Promotes Sprig Mechanisms

CIGRE, general report for high-voltage equipment, table IX, provides reliability data for different types of operating mechanism for SF_6 high-voltage and generator circuit-breakers.

Such data are summarised in the here-below table:

	Major failure rate per 100 CB.years	
Type of operating mechanism	CIGRE	GE
Hydraulic / Hydro-mechanical spring	0.19	/
Pneumatic	0.13	/
Spring	0.11	0.04

GE's spring mechanisms are approximately five times more reliable than hydraulic and hydro-mechanical spring mechanisms and three times more reliable than spring drives from others.



Old Spring Mechanism, 1934

For more information please contact GE Power Grid Solutions

Worldwide Contact Center

Web: www.GEGridSolutions.com/contact Phone: +44 (0) 1785 250 070



Eight decades of experience are continuously supporting the implementation of total quality throughout the entire spring drive process, from engineering to operation, then after-sales.



Spring mechanism routine test station

GEGridSolutions.com

IEC is a registered trademark of Commission Electrotechnique Internationale. CIGRE is a registered trademark of CIGRE.

GE and the GE monogram are trademarks of General Electric Company.

GE reserves the right to make changes to specifications of products described at any time without notice and without obligation to notify any person of such changes.

FK-brochure-EN-2018-06-Grid-GIS-0185. © Copyright 2018, General Electric Company. All rights reserved.

